

Meet the Vollara® Air & Surface Pro XL

Greater Protection for your Indoor Air & Surfaces

THE TECHNOLOGY

The Vollara® Air & Surface Pro XL uses improved combined technologies along with our advanced ActivePure® Technology to effectively treat exposed air and surfaces and improve the quality of indoor air in spaces up to 3,500 square feet. It has been proven to reduce over 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in "The Proof" section below).

ActivePure Technology does not replace the need to follow public health guidelines and should be used as complementary technology.

THE PROOF

In extensive unaffiliated lab testing, ActivePure® Technology has been proven to significantly reduce the following contaminants and pathogens¹:

- SARS-CoV-2
- Staphylococcus aureus
- Aspergillus niger endospores
- H1N1 Influenza
- H5N8 Influenza
- MRSA
- · Bacillus globigii
- · MS2 Bacteriophage
- Staphylococcus epidermidis
- PhiX-174

- Erwinia herbicola
- Listeria monocytogenes
- Murine Norovirus
- E. coli
- Candida auris
- Botrytis cinerea
- · Sclerotinia sclerotiorum
- Legionella pneumophila
- · Aspergillus versicolor
- · Clostridium difficile
- Salmonella enterica

¹View test results at Vollara.com/scientific-proof

ENHANCED FEATURES & BENEFITS

The Vollara® Air & Surface Pro XL provides 24/7 surface decontamination and air purification. It is a proactive and effective solution for your home or business.

- The two 7-inch ActivePure Cells are larger and more powerful in helping to reduce over 99.9% of many surface and airborne contaminants faster
- · A redesigned air tunnel with increased airflow
- Greater Coverage Area of up to 3,500 sq. ft.
- A True HEPA Filter for better filtration and removal of at least 99.97% of dust, pollen, mold, bacteria, and any airborne particles with a size of 0.3 microns
- Both ActivePure Cells are always functioning when the unit is on, giving ActivePure purification and decontamination day and night
- Optional ionization feature assists with particulate removal and can help in the efficiency of the HEPA filtration
- Unit will automatically reset and function at the most recent setting when power is restored after a power failure
- Maintenance Reminders to clean and replace filters and cells – keeps unit running efficiently and effectively





SPECIFICATIONS

Product Information	00772 (ozone-free) Model : B1040C Meets California Ozone Emissions Limit. CARB Certified.
Technology Included	ActivePure® Technology (2 cells) HEPA Filter Activated Carbon Filter Optional Ionization
Electrical	Input Voltage: 100 ~ 240 VAC; 50/60 Hz External Power Supply: DC 24 Volts; 3 Amps Max. Power Consumption: 56 Watts Max.
Mechanical	Nominal Airflow Rate: 40-110 CFM Adjustable Fan Speed
Safety	Conforms to UL 867
Weight & Dimensions	10.4 lbs (4.72 kg) 14.17" H x 11.7" W x 12" D (35.9 cm x 29.7 cm x 30.5 cm)
Operating Temperature	34°F – 100°F (-1°C – 38°C)
Sound Level	45 dB(A) (on low); 57 dB(A) (on high)
Coverage ¹	Up to 3,500 sq. ft. (325 m²) depending on occupant density and other factors. ¹ High density commercial not to exceed 750 sq. ft. (69.7 m²).
Warranty	Limited 3 year warranty



	Contact Name:
	Email:
•	Phone Number:

^{1.} Assumes 8 foot ceilings. Solutions should be customized based upon a variety of factors including HVAC system capabilities and settings, air flows taking into account walls, air pressure, and doors, ambient air temperatures and humidities, variable density, known VOC concentrations, other layers of protection.