

The Vollara Air & Surface Pro reduced 99.96% of airborne SARS-CoV-2, the virus responsible for COVID-19, within 1 minute.¹

This unaffiliated lab test was done on the lowest setting using only the ActivePure® Technology.

THE TECHNOLOGY

The Vollara® Air & Surface Pro combines multiple complementary technologies, including HEPA, activated carbon, and ActivePure® Technology. Patented ActivePure Technology is an advanced air and surface purification technology. It has been proven to reduce up to 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in "The Proof" section below).

ActivePure Technology does not replace the need to follow public health guidelines and should be used as complementary technology.

THE PROOF

In extensive unaffiliated lab testing, ActivePure® Technology has been proven to significantly reduce the following contaminants and pathogens¹:

- SARS-CoV-2
- Staphylococcus aureus
- Aspergillus niger endospores
- H1N1 Influenza
- H5N8 Influenza
- MRSA
- Bacillus globigii
- MS2 Bacteriophage
- Staphylococcus epidermidis
- PhiX-174

- Erwinia herbicola
- Listeria monocytogenes
- Murine Norovirus
- E. coli
- · Candida auris
- Botrytis cinerea
- Sclerotinia sclerotiorum
- Legionella pneumophila
- Aspergillus versicolor
- Clostridium difficile
- Salmonella enterica

THE BENEFITS

The Vollara Air & Surface Pro provides 24/7 air purification and surface decontamination. It is an proactive and effective solution for your home or business.

- Portable, lightweight device
- No installation plug-and-play solution
- · Easy to use and low maintenance
- Proven effective against many common viruses, bacteria, molds, and fungi¹
- Reduces smoke, allergens, odors, and VOC gases without the use of ozone
- Multiple carbon brushes aid in the capture of contaminants



¹View test results at Vollara.com/scientific-proof







2017 Space Technology
Hall of Fame by the Space Foundation





Product Information	9940062 (Ozone-free) Model: A1040B	DOES NOT EXCEED 0.005 PPM AS TESTED BY UL 867
	Meets California Ozone Emissions Limit. CARB Certified.	UL.COM/ECV
	Validated to UL 2998	
Technology Included	ActivePure® Technology – (2) 6" Cells	
	HEPA Filter Screen	
	Activated Carbon Filter	
	Carbon Brushes	
Electrical	Input Voltage: 100 ~ 240 VAC; 50/60 Hz	
	Power Consumption: 43 Watts Max.	
Mechanical	Nominal Airflow Rate: 40-60 CFM; Adjustable Fan Speed	
Safety	Conforms to UL 867	
Weight & Dimensions	7.6 lbs (3.5 kg)	
	11.75" H x 9.5" W x 10" D (29.8 cm x 24.1 cm x 25.4 cm)	
Operating Temperature	34°F – 100°F (1°C – 38°C)	
Sound Level	45 dB(A) (on low); 55 dB(A) (on high)	
Coverage ¹	Up to 2,000 sq. ft. (185 m²) depending on occupant density and other factor	S.
	High density commercial not to exceed 500 sq. ft. (46 m²).	
Warranty	Limited 3 year warranty	
·		



Contact Name:
Email:
Phone Number:

^{1.} Recommended ceiling height to not exceed 10 feet. Solutions should be customized based upon a variety of factors including HVAC system capabilities and settings, air flows taking into account walls, air pressure, and doors, ambient air temperatures and humidities, variable density, known VOC concentrations, other layers of protection.